

ASTAV STRIP PANEL CEILING SPECIFICATIONS

General Description:

Aluminum ceiling panels supported by fully concealed suspension system manufactured in accordance with European standards by ASTAV that have ISO9001:2008, TS EN 13964: 2008 and CE certificates.

Panel Description:

- Raw material: Ceiling panels manufactured from 0,45 mm Aluminum.
- Panel width (mm): 85mm
- Panel length (mm): 5 meters (standard), customised
- Color : Ceiling panels coated electrostatic applied powder coating colored RAL ... (min. 25 µ thickness and approx. %20 Gloss Rate)
- Perforation: imperforated.

Suspension System:

1. As-Carrier® Galvanized Steel Omega Carrier, 0.60mm thickness,
2. As-Carrier® Wall angle "U": Prepainted Galvanized Steel, 0.50mm thickness,
3. As-Carrier® Hanger Spring
4. As-Carrier® Galvanized Hanger: Ø4 mm, 500mm length (Standard)
5. As-Carrier® Sleeve Anchor that coated by zinc against corrosion (optional)

Installation:

As-Carrier® Wall angle "U" should be used for lateral sides facing inwards of the wall. The first hanger system should not exceed 450 mm distance from the wall and the distance between hangers could be max 1000mm. As-Carrier® Clip-in Hanger Spring, As-Carrier® Galvanized Hanger and As-Carrier® Sleeve Anchor will be used to suspend the As-Carrier® Omega Carrier securely. The distance between As-Carrier® Wall angle "U" and As-Carrier® Omega Carrier should be max. 600 mm. The distance between As-Carrier® Omega Carrier should not exceed 1200mm.

ASTAV PANEL ALÜMİNYUM SAN. TİC. LTD. ŞTİ.

Saray Mah. Keresteciler San. Sit. 10.Sokak No: 41, 06980 Kazan / Ankara / Türkiye

Tel : (+90-312) 815 12 42(pbx)

Fax: (+90-312) 354 32 16

e-mail: info@astav.com.tr

web: www.astav.com.tr

Panel 85 Baskı Çıtalı Panel 85 with Press Joint					
Panel 85 Dar Derz Panel 85 Narrow Joint					
Panel 85 Normal Derz Panel 85 Normal Joint					
İkiz Panel Twin Panel					
Panel 200 Strip Panel 200					
Panel 85 Aparatları Panel 85 Parts					
Derz Çıtası Press Joint	Kenar U Profili Wall Angle U Profile	Galvanize Çelik Taşıyıcı Galvanized Steel Carrier	Askı Maşası Quick Fixing	Askı Teli Galvanized Hanger	

Alüminyum Panel 85 1 m²'ye giden malzeme miktarları

Aluminium Strip Panel 85 1 m² Consumption

Ürün Açıklaması Description	Panel/m Panel/m	Derz Çıtası/m Press Joint/m	Kenar "U" Profili/m Wall Angle "U"/m	Galvanize Çelik Taşıyıcı/m Galvanized Steel Carrier/m	Askı Teli/ad. Galvanized Hanger/pcs	Askı Maşası /ad. Quick Fixing (Spring Type)/pcs
Panel 85 Baskı Çıtalı Strip Panel with Press Joint	10	10	1	1	0,83	0,83
Panel 85 Dar Derz (5 mm Boşluklu) Strip Panel Narrow Joint	11	-	1	1	0,83	0,83
Panel 85 Normal Derz (15 mm Boşluklu) Strip Panel without Press Joint	10	-	1	1	0,83	0,83

ASTAV PANEL ALÜMİNYUM SAN. TİC. LTD. ŞTİ.

Saray Mah. Keresteciler San. Sit. 10.Sokak No: 41, 06980 Kazan / Ankara / Türkiye

Tel : (+90-312) 815 12 42(pbx)

Fax: (+90-312) 354 32 16

e-mail: info@astav.com.tr

web: www.astav.com.tr